



NOTES

1. ADJUST LOAD CELL RODS SO THAT SCREW CONVEYOR IS HORIZONTAL.
2. FLEXIBLE CONNECTIONS MUST NOT EXERT INFLUENCE ON CONVEYOR.
3. LOAD CELL AND SPEED SENSOR ARE SUPPLIED WITH JUNCTION BOXES. CONNECTIONS TO THE JUNCTION BOXES MUST BE FLEXIBLE AND NOT EXERT ANY INFLUENCE ON THE CONVEYOR.
4. HORIZONTAL RESTRAINER SHOULD BE LEFT LOOSE WITH APPROXIMATELY 1-2 mm. RESTRAINER PREVENTS EXCESSIVE CONVEYOR MOVEMENT.

REVISIONS A: 4/12/07 ORIGINAL ISSUE	DRAWN	L.H.	 WEB-TECH AUSTRALIA PTY. LTD. <small>11 ELECTRONICS STREET EAST WILEY PLAINS, QUEENSLAND, 4113, AUSTRALIA P.O. BOX 4058 EAST WILEY PLAINS, QUEENSLAND, 4112, AUSTRALIA Phone 481-7-3811 2844 Fax 481-7-3811 0205</small>	SIZE	DRAWING No.
	CHECKED	L.H.		NUMBER	REV.
	APPROVED	L.H.		CUSTOMER	
	DATE APP'D	-		PROJECT	
SCALE	N.T.S.	DO NOT SCALE IF IN DOUBT ASK	CAD FILE		
			PROJECT	SW500001	
			ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE SPECIFIED This drawing and any information or descriptive matter set out hereon are the confidential and proprietary property of WEB-TECH AUSTRALIA PTY. LTD. and must not be disclosed, copied, copied or used for manufacturing / tendering or for any other purpose without their written permission.		